

# 20" Aspen Excelsior Wattles

Erosion logs shall be curled aspen wood excelsior with a consistent width of fibers evenly distributed throughout the log. The casing shall be seamless, photodegradable tube netting and shell conform to the specifications below. The curled aspen wood excelsior shall be fungus-free, resin-free, and shall be free of growth or germination inhibiting substances.



## SPECIFICATIONS\*

**LENGTH**..... 10' Standard

**DIAMETER**..... 20" (+/- 10%)

**CORE**..... Aspen Wood Excelsior with Interlocking Barbs  
80% Fibers at least 6"

**NETTING TYPE**..... U.V. Stabilized/Photodegradable  
Heavy Duty - 94% High-Density Polyethylene  
With 6% UV Inhibitor

**NETTING THICKNESS**..... Strand Thickness of 0.03"  
Knot Thickness of 0.065"

**NETTING WEIGHT**..... 0.90-Ounce Per Foot

**NETTING COLOR**..... Black

**ROLL WEIGHT**..... Average 10' - 40 lbs

**WEIGHT PER L.F.** ..... No Less Than 4 lbs

Our Sediment Control Products are used in a multitude of applications, providing benefits such as:

- Better Filtering of Runoff Waters
- Preventing Check Dam Blowouts
- Protecting Water From Going Around Check Dams
- Preventing the Spread of Non-Native Vegetation
- Easier to Handle and Install than Straw Bales
- Safe to use around livestock: non-food source for animals

\*Verified at time of manufacture

**Distributed By:**



1697 West 2100 North  
Lehi, Utah 84043  
801.768.4422 | 801.561.1456  
Fax 801.768.3967  
info@graniteseed.com  
www.graniteseed.com